

# THREADED ACCESSORIES




**Fig. 60**  
**J-BEAM BOLT**

**FUNCTION:** Designed to provide a means of supporting pipe from the top flange of a beam. Useful in applications where headroom is limited.

**MATERIAL:** Low carbon steel

**FINISH:** Plain

**ORDERING:** Specify rod size, length and figure number.



Rod Size A	Thread Length B	C	Max. Rec. Load/lbs.	Wt. Each (in lbs.)						
				Length D (inches)						
				4	5	6	7	8	10	12
$\frac{3}{8}$	2	$\frac{1}{2}$	240	.19	.22	.25	.28	.32	.38	.44
$\frac{1}{2}$	2	$\frac{5}{8}$	440	.33	.39	.45	.50	.56	.67	.78
$\frac{5}{8}$	$2\frac{1}{2}$	$\frac{3}{4}$	705	.52	.60	.70	.78	.87	1.00	1.20
$\frac{3}{4}$	$2\frac{1}{2}$	$\frac{7}{8}$	1050	.75	.88	1.00	1.10	1.26	1.50	1.75
$\frac{7}{8}$	$2\frac{1}{2}$	1	1500	1.02	1.20	1.35	1.53	1.70	2.00	2.40

Available in stainless steel. To order, specify 304 or 316 and add suffix SS to figure number.

Price on request.