

THREADED ACCESSORIES



TURNBUCKLE

Function: Designed for use as a hanger rod connection on heavy loads when an adjustment of up to 6 (152.4) inches is required.

Material: Forged steel (Type 316 Stainless Steel upon request)

Finish: Plain or electro-galvanized (Hot dipped galvanized upon request)

Approvals: Complies with Federal Specification A-A-1192A (Type 13) and Manufacturers' Standardization Society ANSI/MSS SP-58 (Type 13) which supersedes ANSI/MSS SP-69.

Ordering: Specify figure number, rod size, and finish.

NOTE: Openings of 3"(76.2), 9"(228.6) and 12"(304.8) are available upon request.

Rod Size A	Max. Rec. Load				Wt. Each	
	650°F (343°C)		750°F (399°C)			
	lbs.	kN	lbs.	kN	lbs.	kg
3/8	730	(3.25)	572	(2.54)	.50	(.23)
1/2	1350	(6.01)	1057	(4.70)	.75	(.34)
5/8	2160	(9.61)	1692	(7.52)	1.12	(.51)
3/4	3230	(14.37)	2530	(11.25)	1.75	(.79)
7/8	4480	(19.93)	3508	(15.61)	1.83	(.83)
1	5900	(26.24)	4620	(20.55)	2.60	(1.18)
1 1/8	7450	(33.14)	5834	(25.95)	3.68	(1.67)
1 1/4	9500	(42.26)	7440	(33.09)	4.75	(2.15)
1 1/2	13800	(61.39)	10807	(48.07)	6.25	(2.83)

FIG. 960

